





PRESSURE REDUCING VALVES

PRPS





PRRS

	Pressure Reducing				Pressure Reducing / Relieving		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	PRPS-10-N-S-0-15	46	1030		PRRS-08-N-S-0-15	23	0830
					PRRS-10-N-S-0-15	46	1030
					PRRS-12-N-S-0-30	91	1230

COUNTER BALANCE VALVES





CBPA

CBPS



	Standard 4:1				Sealed Piston 4:1		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	CBPA-08-N-S-0-30	38	0825		CBPS-08-N-S-0-30	38	0825
	CBPA-10-N-S-0-30	76	1025		CBPS-10-N-S-0-30	76	1025
	CBPA-12-N-S-0-30	132	1225		CBPS-12-N-S-0-30	132	1225

CBPG

CBPA-20M (Also available in **CBPG-20M** & **CBPS-20M**)

	Vented Piston 4:1				As Standard to suit Sun Cavity 4:1		
	Part Number	Flow L/min	Cavity		Part Number	Flow L/min	Cavity
	CBPG-08-N-S-0-30	38	0825		CBPA-20M-N-S-0-15	76	T-11A
	CBPG-10-N-S-0-30	76	1025		CBPA-20M-N-S-0-30		
	CBPG-12-N-S-0-30	132	1225		CBPA-20M-N-S-0-50		

CBPP

	Standard 10:1		
	Part Number	Flow L/min	Cavity
	CBPP-10-N-S-0-10-30-C	60	1025
	CBPP-20M-N-S-0-10-30C		T-11A

NB: The above Cartridges available in the following pressure range - substitute the last 2 numbers.

15 = 50 to 1500 psi (3.5 to 103 bar)

30 = 100 to 3000 psi (7 to 206 bar)

40 = 600 to 4000 psi (28 to 275 bar) (Applicable only to size 12 counter-balance valves)

50 = 1500 to 5000 psi (103 to 345 bar) (NOT applicable to size 12 counter-balance valves)

Use the cavity size to select the correct body type then choose the desired port size.