



RELIEF VALVES


RVPD

	Direct Acting - Pilot Type		
	Part Number	Flow L/min	Cavity
	RVPD-08-N-S-0-30	7.6	0820
	RVPD-10-N-S-0-30	7.6	1020


RVDI

	Direct Acting - Poppet Type		
	Part Number	Flow L/min	Cavity
	RVDI-10-N-S-0-30	76	1020


RVPS

	Piloted Spool		
	Part Number	Flow L/min	Cavity
	RVPS-08-N-S-0-30	58	0820
	RVPS-10-N-S-0-30	100	1020
	RVPS-12-N-S-0-30	230	1220


RVPP

	Piloted Poppet & Reverse		
	Part Number	Flow L/min	Cavity
	RVPP-10-N-S-0-30	100	1020
	RVPP-12-N-S-0-30	230	1220


RVBD

	Bi-Directional		
	Part Number	Flow L/min	Cavity
	RVBD-08-N-S-0-30	38	0820
	RVBD-10-N-S-0-30	76	1020
	RVBD-12-N-S-0-30	150	1220


RVBS

	Breaker - Pilot Op.		
	Part Number	Flow L/min	Cavity
	RVBS-10-N-S-0-30	95	1020

PUVA

	Unloading Relief With Differential		
	Part Number	Flow L/min	Cavity
	PUVA-10-N-S-0-8-40 (80%)	4	1030

RVDA

	Differential Area		
	Part Number	Flow L/min	Cavity
	RVDA-08-N-S-0-30	38	0820
	RVDA-10-N-S-0-30	76	1020

NB: The above cartridges are available in the following pressure range. Substitute the last 2 numbers.
 15 = 50 to 1500 psi (3.5 - 103 bar)
 30 = 100 to 3000 psi (7 - 206 bar)
 50 = 150 to 5000 psi (10 - 345 bar)

Use the cavity size to select the correct body type then choose the desired port size.